




RaycoWylie
SYSTEMS

i 4000

**MULTI-PURPOSE INDICATOR
RANGE LIMITING DEVICE**



www.RaycoWylie.com

Different ways to see the information



All information available at a glance



Easy data transfer by USB



Range limiting with dedicated lock-out

Features

- Continuous display of load on hook, current hoist selected and part of lines settings
- Compatible with most existing sensors
- Diagnostic menu and continuous error detection and recording
- Audible and visual alarms indicating two-block, load limit conditions and range limiting device
- Adjustable high and low angle, load, length and wind speed limits
- Optional lock-out for load, A2B and range limiting device
- Easy calibration via keypad. No additional programming hardware necessary
- Quick and easy installation
- USB port for updates
- 3 languages interface : English, Spanish, French [other languages available upon request]
- Selectable units
- Upgradable to the i4500 Series

Technical Data

- Display size: 6.15 x 3.56 x 2.36 inches (15.61 x 9.03 x 5.99 cm)
- Screen size: 3.5 inch LCD Color Screen (320 x 240)
- Display Rating : IP67
- Supply Voltage : 10 to 30 Vdc
- Operating temperature : -4°F to 140°F (-20°C to 60°C)
- Extended temperature : -40°F to 140°F (-40°C to 60°C)
- CANbus communication link J1939

Sensors Available

LOAD SENSORS



LOAD LINK



LOAD PINS



DYNAMOMETER

OTHER SENSORS



ANGLE SENSOR



A2B SWITCH



WIND SPEED SENSOR



ABSOLUTE SLEW SENSOR

CABLE REELS



MINI REEL
(10FT / 3M EXT)



X-SMALL REEL
(40FT / 12M EXT)



MEDIUM REEL
(80FT / 24M EXT)



LARGE REEL
(160FT / 49M EXT)



www.RaycoWylie.com
sales@raycowylie.com

Drury Lane,
St.Leonards-on-Sea, East Sussex,
TN38 9BA, United Kingdom
Tel: +44(0) 1424 421235
Fax: +44(0) 1424 433760

1020 9th avenue S.W. Suite 125,
Bessemer AL, USA, 35022
Toll free: 1-888-252-1957
Tel: (205) 481-2080
Fax: (205) 481-2081

2440 ave Dalton, Sainte-Foy,
(Qc), Canada, G1P 3X1
Toll free: 1-800-563-6137
Tel: (418) 266-6600
Fax: (418) 266-6610

Carrera 22, No.150-59
Bogotá, Colombia
Tel : (571) 6278690
Tel: (57) 3115970345